

# XA-MULTI 236.14

## SYNTHETIC AUTOMATIC TRANSMISSION FLUID

### DESCRIPTION

XA-MULTI 236.14 is a hybrid-synthetic-technology lubricant based on high-tech additives and a special selection of synthetic base oils. Guarantees highest performance and protection even in extreme operating conditions. XA-Multi 236.14 is engineered for most modern automatic transmission (manual mode, sequential mode, electronically controlled) with or without slip lockup clutch.



### PROPERTIES

- Protects the compact and heavily loaded gears thanks to advanced anti-wear properties.
- Allows fuel economy by reducing epicyclical gears friction.
- Gives superior transmission response: smooth shift feel and minimizing shift time lag.
- Extends life time duration, high shear stability at hot temperature and oxidation resistance.
- Constant friction stability over lifetime ensuring perfect clutch operation.
- Prevents from shudder shifting problems.
- Excellent low temperature shifting performance.
- Reduced foaming tendency.

### APPLICATION

This fluid may be used for automatic transmissions of various car manufacturers. Especially recommended for use in all Mercedes vehicles fitted with the 7 speed RWD automatic transmissions (NAG2) and all AMG models, as well as Mercedes 5 speed automatic transmissions with regulated torque converter lockup clutch, where MB-Approval 236.14 specification is required. Apply the recommended amount of oil as indicated in the manufacturer's service instructions. Wrong oil level could cause damage.

### TYPICALS

Density at 15 °C, kg/l	0,855
Viscosity 40 °C, mm²/s	29,60
Viscosity 100 °C, mm²/s	6,55
Viscosity Index	185
Flash Point COC, °C	200
Pour Point, °C	-60

### PACKAGING

1L can (12 x 1L carton)  
60 L drum  
208 L drum

### SPECIFICATIONS

Allison C4, Chrysler ATF+3  
Dexron II/IID/IIIE/IIIG/IIIH, Ford WSS-M2C922-A1  
Honda Z-1, Hyundai SP-II/SP-III  
Isuzu ATF II/III, Jaguar JLM 20238/20292/21044  
JASO Type 1A, Kia SP-II/SP-III  
Mazda M-III/Type T-IV  
MB 236.10/236.12/236.14  
MB 236.3/236.6/236.7/236.8/236.9/236.11/236.91  
Mitsubishi SP-II/SP-III/ATF J-2  
Nissan Matic D/J/K/W  
Subaru ATF/ATF HP, Suzuki ATF 3314/3317  
Toyota Type DII/T/T-III/T-IV  
VAG G-055-025/G-052-162  
Volvo 1161540

Also recommended for vehicles that require:  
ZF 6HP / 5HP / 4HP