

## SEMIX 5w40

### HYBRID SYNTHETIC MOTOR OIL

#### DESCRIPTION

Universal, fuel economy, specially composed hybrid synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans.

#### PROPERTIES

- High and stable viscosity index.
- High resistance against shearing.
- Fast and safe cold start.
- Excellent fluidity at low temperature.
- Fuel economy and CO2 reduction.
- Strong resistance and protection against wear.
- Powerful detergency prevents deposits in the engine.
- Safe lubrication film.
- Very strong resistance against oxidation.

#### APPLICATION

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers. Not suited for cars equipped with a DPF.

#### TYPICALS

Density at 15 °C	0,853 kg/l
Viscosity -30 °C	5740 mPa.s
Viscosity 40 °C	90,20 mm²/s
Viscosity 100 °C	15,00 mm²/s
Viscosity index	175
Flash point COC	223 °C
Pour point	-42 °C
Total base number	10,5 mgKOH/g
Sulphated ash	1,33 %

#### SPECIFICATIONS

API: SN/CF  
ACEA: A3/B4  
VW 502.00 / 505.00  
MB 229.3 / 226.5  
BMW: Longlife-01  
OPEL GM-LL-B-25  
RENAULT RN 0700, RN 0710  
Fiat 9.55535-M2  
Porsche A40  
PSA B71 2296

#### PACKAGING

1L can (12 x 1L box)  
5L can (4 x 5L box)  
20 L can  
60 L drum  
208 L drum

