

XT-PRO 75w140 LS

TRANSMISSION OIL

DESCRIPTION

XT-PRO 75W140 LS is a 100% synthetic hypoid transmission oil with "limited slip" additives. Designed specifically to the extreme demands of the various motorsports for use in differentials, both with and without multiple disk systems and transmissions subject to very heavy loads as used in various motor sports.

PROPERTIES

- High viscosity index to guarantee high fluidity at low temperatures.
- Outstanding resistance to oxidation, providing optimum protection against high operating temperatures.
- Very low foaming propensity.
- Outstanding wear protection.
- Ideally suited for use in self-locking differentials owing to special "limited slip" additives

APPLICATION

XT-PRO 75W140 LS is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. Can also be used in all differentials of the various BMW M-Sport models and in the differentials of various SUVs for which SAE 75W140 hypoid oil is prescribed. Apply the correct amount of oil indicated in the service instructions of the manufacture. Wrong amount of oil can cause damage to the transmission.

TYPICALS

Density at 15 °C	0,905 kg/l
Viscosity 40 °C	170,00 mm ² /s
Viscosity 100 °C	26,50 mm ² /s
Viscosity index	195
Flash point COC	160 °C
Pour point	-51 °C

SPECIFICATIONS

API GL 4+, GL-5 / LS
MIL MIL-L-2105 E
BMW MSP/A
SCANIA STO 1.0 box
MAN 341 Z2, 341 E3, 342 M3
MB 235.8
ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
IVECO axles
VOITH 3.325-340
Arvin Meritor O-76N
INTERNATIONAL TMS-6816

DAFPACKAGING

1L can (12 x 1L carton)
5L can (4 x 5L carton)
20 L drum
60 L drum
208 L drum

