

# X-TRAN 75w90 GL4/5

## TRANSMISSION OIL

### DESCRIPTION

Synthetic multi-purpose, X-TRAN 75W-90 GL4/5 automotive gear lubricant designed to meet the highest level performance requirements of modern passenger vehicles in all types of operating conditions. Compared to conventional hypoid gear lubricants, X-TRAN 75w90 GL4/5 performs exceptionally over a wide range of temperatures. It also can be used in extended service and for aiding in fuel economy performance.

For manual gearboxes, power steering units, torque converters and other hydraulic equipment.

### PROPERTIES

- Exceptional thermal stability and resistance to high temperature oxidation
- Maintains film strength for reliable lubrication
- Exceptional shear stability
- Excellent rust, staining and corrosion protection of copper and its alloys
- Outstanding protection against low speed/high torque wear and against high speed scoring
- Enhanced frictional properties
- Reduced wear & longer component life

### APPLICATION

This oil is mainly used in hypoid rear axles with a limited-slip mechanism, and transfer boxes of high power cars, SUV's and all-wheel drives (AWD). Suitable for SAE 75W90 and 75W85 applications.

### TYPICALS

Density at 15 °C	0,874 kg/l
Viscosity 40 °C	78,80 mm <sup>2</sup> /s
Viscosity 100 °C	14,40 mm <sup>2</sup> /s
Viscosity Index	192
Flash Point COC	172 °C
Pour Point	-45 °C

### SPECIFICATIONS

API: GL 4+, GL-5 / LS  
MIL: MIL-L-2105 E  
SCANIA STO 1.0 box  
MAN 341 Z2, 341 E3, 342 M3  
MB 235.8  
ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B  
IVECO axles  
VOITH 3.325-340  
Arvin Meritor O-76N  
INTERNATIONAL TMS-6816  
DAF

### PACKAGING

1L can (12 x 1L carton)  
5L can (4 x 5L carton)  
60 L drum  
208 L drum

