

XA-TRAN CVT

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

High performance synthetic fluid specially engineered for Continuously Variable Transmission (CVT) gearboxes. XA-TRAN CVT is made of precisely selected base oils and special additives. Suitable for use in a wide range of vehicles equipped with CVT transmissions of both chain/pulleys or belt/pulleys design.

PROPERTIES

- Allows fuel economy for cars fitted with CVT gearboxes by providing optimum metal-to-metal friction.
- Superior response through smooth shift feel and reduced shift time lag.
- Provides optimum anti-shudder performance and avoids engine vibrations.
- Improves cold temperature performance.
- Extended service interval in combination with a longer transmission life.
- Strong reduction of wear, corrosion, oxidation and foam.
- Ideal friction performance, for both CVT belt and CVT chain.

APPLICATION

XA-TRAN CVT is recommended for use in a wide range of CVT-Transmission types. Apply the recommended amount of oil as indicated in the manufacturer's service instructions. Wrong oil level could cause damage.

TYPICALS

Density at 15 °C	0,852 kg/l
Viscosity -40 °C	10600 mPa.s
Viscosity 40 °C	34,20 mm ² /s
Viscosity 100 °C	7,35 mm ² /s
Viscosity Index	189
Flash Point COC	210 °C
Pour Point	-45 °C

SPECIFICATIONS

AUDI: TL 52180
Daihatsu Ammix CVT
DODGE: NS-2/CVTF+4
FORD: CVT23, CVT30, MERCON C
GM: SATURN DEX-CVT
HONDA: HCF-2, HMMF
HYUNDAI: SP-CVT1, SP-III
JEEP: NS-2/CVTF+4
KIA: SP-CVT 1, SP-III
MB: 236.20
MINI: EZL799A
BMW: 83220136376 / 83220429159
MITSUBISHI: CVTF-J1/SP-III
NISSAN: NS-1, NS-2, NS-3
PUNCH: EZL799A
SUBARU: Lineartronic CVTF
SUZUKI: TC/NS-2/CVT Green 1
TOYOTA: TC
VW: G 052 180, G 052 516

PACKAGING

1L can (12 x 1L carton)
20L drum
60 L drum
208 L drum

