

XA-TRAN NIPPON

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Top tier synthetic automatic transmission fluid. Designed for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications.

PROPERTIES

- Very high and stable viscosity index.
- Very low pour point.
- Excellent oxidation stability.
- Outstanding anti-wear properties.
- Outstanding performances at cold start conditions.
- Specific friction properties and consequently low noise and smooth switching.

APPLICATION

This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

TYPICALS

Density at 15 °C	0,846 kg/l
Viscosity 40 °C	36,60 mm ² /s
Viscosity 100 °C	7,20 mm ² /s
Viscosity Index	165
Flash Point COC	212 °C
Pour Point	-48 °C
Total Base Number	2,7 mgKOH/g

SPECIFICATIONS

Nissan Matic Fluid C/D/J/K
Toyota ATF T/ T-II/T-III/T-IV/D-II/D-III/WS
Honda ULTRA II, ULTRA-Z1, ULTRA HMMF
Mazda ATF M-V
Hyundai/Kia SP-II/SP-III
Suzuki ATF 3314
Subaru ATF/ATF 5AT/ATF HP/Dexron II
GM Dexron IID/IIE/IIIG/IIIH, TASA
Ford Mercon/M2C 138CJ/166H/922A1/924^a
Aisin Warner JWS 3309/3324, Isuzu Besco ATF II/III
Allison C4/TES-228, JASO M 315-2013 Type 1^a
MB 236.1/236.6/236.7/236.8/236.9/236.10
BMW 7045E/8072B
Chrysler ATF +3/ATF +4
VAG G-055-025
Volvo 1161540
ZF TE-ML 09/11A/11B

PACKAGING

1L can (12 x 1L carton)
20L drum
60 L drum
208 L drum

